

Industries Products Insights Events Ecosystem Data Security Support Contact U

Matrice 350 RTK Specs Video Downloads FAQ Buy Now

# Specs

## Aircraft

Dimensions (unfolded, without propellers)

810×670×430 mm (L×W×H)

Dimensions (folded, with

propellers)

430×420×430 mm (L×W×H)

Diagonal Wheelbase

895 mm

Weight (with single downward

gimbal)

Without batteries: Approx. 3.77 kg

With two TB65 batteries:

Approx. 6.47 kg

Single Gimbal Damper's Max

**Payload** 

960 g

9.2 kg

Max Takeoff Weight

Operating Frequency 2.4000-2.4835 GHz

5.150-5.250 GHz (CE: 5.170-5.250 GHz)

5.725-5.850 GHz

 $In some countries \ and \ regions, the 5.1 GHz \ and \ 5.8 GHz \ frequency \ bands \ are \ prohibited, or the 5.1 GHz \ frequency \ band \ is \ only \ allowed \ for \ indocenter \ frequency \ bands \ are \ prohibited, or the 5.1 GHz \ frequency \ band \ is \ only \ allowed \ for \ indocenter \ frequency \ bands \ are \ prohibited, or the 5.1 GHz \ frequency \ bands \ is \ only \ allowed \ for \ indocenter \ frequency \ bands \ are \ prohibited, or the 5.1 GHz \ frequency \ bands \ is \ only \ allowed \ for \ indocenter \ frequency \ bands \ are \ prohibited, or \ the 5.1 GHz \ frequency \ bands \ is \ only \ allowed \ for \ indocenter \ frequency \ bands \ are \ frequency \ are \ frequency \ bands \ are \ fre$ 

refer to local laws and regulations for more information.

**Transmitter Power (EIRP)** 2.4000-2.4835 GHz:

< 33 dBm (FCC)

< 20 dBm (CE/SRRC/MIC)

5.150-5.250 GHz (CE: 5.170-5.250 GHz):

< 23 dBm (CE)

5.725-5.850 GHz: < 33 dBm (FCC/SRRC) < 14 dBm (CE) Hovering Accuracy (with moderate

or no wind)

Vertical:

±0.1 m (with vision positioning) ±0.5 m (with GNSS positioning) ±0.1 m (with RTK positioning)

Horizontal:

±0.3 m (with vision positioning) ±1.5 m (with GNSS positioning) ±0.1 m (with RTK positioning)

RTK Positioning Accuracy (RTK FIX) 1 cm + 1 ppm (horizontal)

1.5 cm + 1 ppm (vertical)

Max Angular Velocity

Pitch: 300°/s Yaw: 100°/s

Max Pitch Angle

30°

When in N mode and with the forward vision system enabled: 25°.

Max Ascent Speed

6 m/s

Max Descent Speed (vertical)

5 m/s

Max Tilted Descent Speed

7 m/s

Max Horizontal Speed

23 m/s

Max Flight Altitude

5000 m

When using the 2110s propellers and with the takeoff weight  $\leq$  7.4 kg.

7000 m

When using the 2112 High-Altitude Low-Noise Propellers and with the takeoff weight  $\leq$  7.2 kg.

Max Wind Speed Resistance

12 m/s

Max Flight Time

55 minutes

Measured with Matrice 350 RTK flying at approximately 8 m/s without payloads in a windless environment until the battery level reached 0%. D reference only. Actual usage time may vary depending on the flight mode, accessories, and environment. Please pay attention to reminders in t

Supported DJI Gimbals

Zenmuse H30, Zenmuse H30T, Zenmuse H20, Zenmuse H20T, Zenmuse H20N, Zenmuse L2, Zenmuse L1, aı

Zenmuse P1

Third-Party Payload

Supports only certified payloads developed based on DJI Payload SDK.

**Supported Gimbal Configurations** 

Single downward gimbal Single upward gimbal Dual downward gimbals

Single downward gimbal + single upward gimbal Dual downward gimbals + single upward gimbal

**Ingress Protection Rating** 

IP55

The IP rating is not permanently effective and may decrease due to product wear and tear.

Global Navigation Satellite System

GPS + GLONASS + BeiDou + Galileo

**Operating Temperature** 

-20° to 50° C (-4° to 122° F)

Class

C3 (EU)

#### Remote Controller

Screen 7.02-inch LCD touchscreen; resolution: 1920×1200; max brightness: 1200 nits

Weight Approx. 1.25 kg (without WB37 battery)

Approx. 1.42 kg (with WB37 battery)

Global Navigation Satellite System GPS + Galileo + BeiDou

Built-in Battery Type: Li-ion (6500 mAh@7.2 V)

Charging Type: Use the battery station or USB-C fast charger with a max power of 65 W (max voltage of 20 \

Charging Time: 2 hours Chemical System: LiNiCoAlO2

External Battery (WB37 Intelligent

Battery)

Capacity: 4920 mAh Voltage: 7.6 V Type: Li-ion

Energy: 37.39 Wh Chemical System: LiCoO2

Ingress Protection Rating IP54

**Operating Time** Built-in Battery: approx. 3.3 hours

Built-in Battery + External Battery: approx. 6 hours

Operating Temperature -20° to 50° C (-4° to 122° F)

**Operating Frequency** 2.4000-2.4835 GHz

5.725-5.850 GHz

Transmitter Power (EIRP) 2.4000-2.4835 GHz:

< 33 dBm (FCC)

< 20 dBm (CE/SRRC/MIC)

5.725-5.850 GHz: < 33 dBm (FCC) < 14 dBm (CE) < 23 dBm (SRRC)

Wi-Fi Protocol Wi-Fi 6

Wi-Fi Operating Frequency 2.4000-2.4835 GHz

5.150-5.250 GHz 5.725-5.850 GHz

**Bluetooth Protocol** Bluetooth 5.1

Bluetooth Operating Frequency 2.4000-2.4835 GHz

#### Video Transmission

Video Transmission System DJI O3 Enterprise Transmission

Antenna 4 video transmission antennas, 2T4R

Max Transmission Distance (unobstructed, free of interference) 20 km (FCC) 8 km (CE/SRRC/MIC)

Max Transmission Distance (with interference)

Low Interference and Obstructed by Buildings: approx. 0-0.5 km Low Interference and Obstructed by Trees: approx. 0.5-3 km

Strong Interference and Unobstructed: urban landscape, approx. 1.5-3 km Medium Interference and Unobstructed: suburban landscape, approx. 3-9 km Low Interference and Unobstructed: suburb/seaside, approx. 9-20 km

Measured with FCC compliance in unobstructed environments with typical interference at a flight altitude of approximately 120 m. Data is for reconly. The actual transmission distance may vary depending on the environment's obstruction and interference conditions. Please pay attention reminders in the app.

## **Vision System**

Obstacle Sensing Range Forward/Backward/Left/Right: 0.7-40 m

Upward/Downward: 0.6-30 m

FOV Forward/Backward/Downward: 65° (horizontal), 50° (vertical)

Left/Right/Upward: 75° (horizontal), 60° (vertical)

**Operating Environment** Surfaces with discernible patterns and adequate lighting (lux > 15)

## **Infrared Sensing System**

Obstacle Sensing Range 0.1-8 m

FOV 30° (±15°)

Operating Environment Large, diffuse, and reflective obstacles (reflectivity > 10%)

## **LED Auxiliary Light**

Effective Illumination Distance 5 m

Illumination Type 60 Hz, solid glow

#### **FPV Camera**

Resolution 1080p

**FOV** 142°

Frame Rate 30fps

## **Intelligent Flight Battery**

Model TB65

Capacity 5880 mAh

Voltage 44.76 V

Type Li-ion

Energy 263.2 Wh

Weight Approx. 1.35 kg

Operating Temperature -20° to 50° C (-4° to 122° F)

Ideal Storage Temperature 22° to 30° C (71.6° to 86° F)

Charging Temperature -20° to 40° C (-4° to 104° F)

When the ambient temperature is below 5° C (41° F), the battery will trigger the auto-heating function. Charging at low temperatures may reduce

life. It is recommended to charge at 15° to 35° C (59° to 95° F).

Charging Time With a 220V power supply, it takes approximately 60 minutes to fully charge two TB65 Intelligent Flight Batte

approximately 30 minutes to charge them from 20% to 90%.

With a 110V power supply, it takes approximately 70 minutes to fully charge two TB65 Intelligent Flight Batti

approximately 40 minutes to charge them from 20% to 90%.

## **Intelligent Battery Station**

**Dimensions** 580×358×254 mm (L×W×H)

Net Weight Approx. 8.98 kg

Compatible Stored Items Eight TB65 Intelligent Flight Batteries

Four WB37 Intelligent Batteries

Input Voltage 100-120 VAC, 50-60 Hz

220-240 VAC, 50-60 Hz

Max Input Power 1070 W

**Output Power** 100-120 V: 750 W

220-240 V: 992 W

Operating Temperature  $-20^{\circ}$  to  $40^{\circ}$  C (-4° to  $104^{\circ}$  F)

#### **Footnotes**

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are tracer registered trademarks of HDMI Licensing Administrator, Inc.



## **Others**

Guaranteed software updates

2025/12/31

until

Product Categories Where to Buy Fly Safe Explore Community

Consumer	DJI Online Store	Fly Safe	Newsroom	SkyPixel
Professional	Flagship Stores	DJI Flying Tips	Events	DJI Forum
Enterprise	DJI-Operated Stores	Support	Buying Guides	Developer
Components	Retail Stores	Product Support	STEAM Education	Subscribe
Service Plan	Enterprise Retailers	Repair Services	Mini Drones	Get the latest news fron
DJI Care	Agricultural Drone Dealer	Help Center	DJI Camera Drones	Your email addres
Osmo Shield	Pro Retailers	After-Sales Service Policies	DJI Affiliate Program	

Download Center

Security and Privacy

DJI Entertainment

رزع

Who We Are

Contact Us

Copyright © 2024 DJI All Rights Reserved. Feedback on web experience

DJI Care Refresh

Dealer Portal

RoboMaster

Apply For Authorized Store

DJI Privacy Policy  $\,\cdot\,\,$  Use of Cookies  $\,\cdot\,\,$  Terms of Use  $\,\cdot\,\,$  Site Map  $\,\cdot\,\,$  Business Information  $\,\cdot\,\,$  Cookie Preferences

Careers

DJI Store App

Cooperation Become a Dealer

⊕ En,